

KAYAK PADDLE – TOURING

MODEL	CONFIGURATION (**)	SIZE	OFFICIAL	
			NO VAT	VAT (22%)
LOW ANGLE	- S – 1P	650	216.39	264
	- S – 2P	650	241.80	295
	- S – 1P – OI	650	225.41	275
	- S – 2P – OI	650	250.82	306
	- S – 2P – APL	650	250.82	306
	- S – 2P – OI - APL	650	259.02	316



HIGH ANGLE	- S – 1P	720 / 670 / 620	216.39	264
	- S – 2P	720 / 670 / 620	241.80	295
	- S – 1P – OI	720 / 670 / 620	225.41	275
	- S – 2P – OI	720 / 670 / 620	250.82	306
	- S – 2P – APL	720 / 670 / 620	250.82	306
	- S – 2P – OI - APL	720 / 670 / 620	259.02	316



ALL ROUND	- S – 1P	640 (new)	72.13	88
	- S – 2P	640 (new)	80.33	98



+ PADDLE COVER (RED OR ANTHRACITE)			16.39	20
------------------------------------	--	--	-------	----



PADDLE CONFIGURATION ()**
 S 1P : STRAIGHT SHAFT 1 PIECE
 S 1P OI : STRAIGHT SHAFT 1 PIECE OVAL INDEX
 S 2P : STRAIGHT SHAFT 2 PIECES
 S 2P OI : STRAIGHT SHAFT 2 PIECES OVAL INDEX
 S 2 P OI APL : STRAIGHT SHAFT 2 PIECES OVAL INDEX ALUMINUM PADDLE LOCK
SHAFT OPTION

FLEX 6 Ø28/ Ø29, FLEX 6 WITH OVAL INDEX Ø28 / Ø29, FLEX 4 Ø 28/ Ø29

RECOMMENDED SHAFT STIFFNESS: : We recommend stiffer shafts for bigger blades but any combination is possible